

Type schakel	afdichting-bereik	schakel-lengte	minimale muurdikte	inbouw-lengte	sleutel-wijdte
DG 100	9,0 – 12,5	31,4	50	64	2,5 inbus
DG 200	12,5 – 16	30,5	50	64	4 inbus
DG 215	12,5 – 16	43,3	50	64	4 inbus
DG 250	15,5 – 20	28,8	50	64	4 inbus
DG 265	15,5 – 20	42,4	50	64	4 inbus
DG 300	17,0 – 23	40,3	70	90	5 inbus
DG 310	17,0 – 23	57,1	70	90	5 inbus
DG 315	20,5 – 27	37,7	70	90	5 inbus
DG 365	20,5 – 27	55,9	70	90	5 inbus
DG 325	24,5 – 33	77	70	101	6 inbus
DG 350	24,5 – 33	41,9	70	101	6 inbus
DG 425	28,5 – 38	93	100	136	8 inbus
DG 375	31,5 – 40	55,5	70	101	6 inbus
DG 465	31,5 – 40	93	100	136	8 inbus
DG 400	36,5 – 46	93	100	136	8 inbus

Type schakel	afdichting-bereik	schakel-lengte	minimale muurdikte	inbouw-lengte	sleutel-wijdte
DG 415	36,5 – 46	68	100	136	8 inbus
DG 450	40,5 – 51	92	100	136	8 inbus
DG 475	40,5 – 51	68	100	136	8 inbus
DG 480	44,5 – 54	142	100	136	8 inbus
DG 525	48,5 – 60	99	110	151	10 inbus
DG 550	48,5 – 60	78,5	110	151	10 inbus
DG 500	58,5 – 72	99	110	151	10 inbus
DG 565	58,5 – 72	78,5	110	151	10 inbus
DG 650	70,5 – 84	104	110	151	10 inbus
DG 665	70,5 – 84	160,1	110	151	10 inbus
DG 600	81,0 – 100	101	110	151	10 inbus
DG 615	81,0 – 100	157	110	151	10 inbus
DG 675	86,0 – 102	109,5	110	151	10 inbus
DG 800	128 – 145	167,5	110	151	10 inbus
DG 865	143 – 165	167,5	110	151	10 inbus